

C 200 Open

| Technical Data | |
|---|--|
| up to approx. 25 to / 55000 lbs take off weight | |
| Engine | YANMAR 45 HP Cylinders 4 water cooled power KW/PS 35,4 / 48,1 boring 88 x 90 upstroke 2,2 L U/ min max. 2700 Concentration 22 full ca. Std. 10,5 L Injection system Bosch K |
| Truck specifications | Speed: ca. 10 km/h operations: Joystick operations, wheel drive for each continuously, forward and backward, steering left and right. Transmission: hydraulic traction drive with four wheel drive Steering: electric Steering operated by Joystick Electronic: Seefried, Hatz engine electronic Battery: 12 V 120 AH |
| Weight | max. weight 6120 kg Truck empty weight: 1810 kg Empty weight front 1150 kg Empty weight back 660 kg Pick up weight max.: 4100 kg |
| Transmission | Sauer Danfoss or Hydag Hydraulic single wheel drive for each continuously forward and backward, Continuously variable speed |
| Cabin | Without Cabin, open working platform, with safty equipment. |
| Tire | 195/50-B10, double tire wheels drive 15x6.00 Block, double tire steering axis . |
| Landing gear bracket | Change-rack with lock, electric – hydraulics rack, with hydraulics-clutch for expandable lifts - and work-cylinders. |
| Light tools | <ul style="list-style-type: none"> ➤ Driver and movable working lights, ➤ Safety up turn lights on top, ➤ Signal horn, |
| additional equipment | docking - supervision, TFT 5,5 `collar TV, Magnet, safety lock getting for Cessna Citation Battery-supervision-system CTEK, others * Remote control for all substantial operations, drive forward and backward, steering, pick up, lift up and down, Nose gear fixation |
| Universal-receptacle | For double front landing gear, up to width tire 410 mm with bled pulling operated |
| Adapted for | Falcon, Gulfstream, Embraer, Cessna, Beech, Lear Jet, till MTOW 25 t. |

Please contact the distributor in your country for prices. You can find your distributor at the button contact.



Additional equipment

Price on application

Cessna Citation Rack with hydraulic side push and magnet lock

Universal receptacle 270 for single front landing gear, up to width tire 270 mm with belt pulling operated

Universal receptacle 410 for double front landing gear, up to width tire 410 mm with belt pulling operated

Commercial receptacle for single and double front landing gear, up to width tire 650 mm, with hydraulic front gear wheel hold system, hydraulic door closing system

Battery-supervision-System CTEK observing with docking station for 230 V

Docking supervision TFT 5,5" Zoll colour TV

GPU RB75A Twin

Flyer-Truck

Ground Handling Systems
Maschinenbau Konrad Zaglauer

Tel. +49 (0) 8635 273
info@flyertruck.de
www.flyer-truck.com