

C 250 Airport

Technical Data	
up to approx. 35 to / 77000 lbs take off weight	
Engine	YANMAR 62 HP Turbo Cylinders 4 water cooled power KW/PS 45,6 / 62,0 boring 98x110 upstroke 3,3 L Turbo U/ min max. 1800 Concentration, full ca. Std. 13,8 L Injection syst. Bosch K
Truck specifications	Speed: ca. 28 km/h operations: Joystick operations, wheel drive for each continuously forward and backward, steering left and right. Transmission: hydraulic traction drive with four wheel drive Steering: electric Steering operated by Joystick Electronic: Seefried, Yanmar engine electronic Battery: 12 V 120 AH
Weight	max. weight 6370 kg Truck empty weight: 3250 kg Empty weight front 1940 kg Empty weight back 1310 kg Pick up weight max.: 6500 kg
Transmission	Sauer Danfoss or Hydag Hydraulic single wheel drive for each continuously forward and backward, Continuously variable speed
Tire	195/50-B10, double tire wheels drive 15x6.00 Block, double tire steering axis .
Cabin	Driver cabin for one Operator with ergonomically situated operating elements, Side Door and 360° range of vision
Landing gear bracket	Change-rack with lock, electric – hydraulics rack, with hydraulics-clutch for expandable lifts - and work-cylinders,.
Light tools	<ul style="list-style-type: none"> ➤ Driver and movable working lights, ➤ Safety up turn lights on top, ➤ Windshield wipers in the front and behind with wash ➤ Worm windshield behind, ➤ Signal horn,
additional equipment	docking - supervision, TFT 5,5 ` collar TV, Magnet, safety lock getting for Cessna Citation Battery-supervision-system CTEK, others * Remote control for all substantial operations operations, drive forward and backward, steering, pick up, lift up and down, Nose gear fixation
admission	In work
Universal-receptacle	For double front Landing Gear up to width tire 650 mm With hydraulic front Gear wheel hold system
Adapted for	Do 328, Dasch 8, Falcon, Gulfstream, Embraer, Cessna, Beech, Lear Jet, till MTOW 35 t.

Please contact the distributor in your country for prices. You can find your distributor at the button contact.



Additional equipment

Price on application

Cessna Citation Rack with hydraulic side push and magnet lock

Universal receptacle 270 for single front landing gear, up to width tire 270 mm with belt pulling operated

Universal receptacle 410 for double front landing gear, up to width tire 410 mm with belt pulling operated

Commercial receptacle for single and double front landing gear, up to width tire 650 mm, with hydraulic front gear wheel hold system, hydraulic door closing system

Battery-supervision-System CTEK observing with docking station for 230 V

Docking supervision TFT 5,5" Zoll colour TV

GPU RB75A Tribble

Flyer-Truck

Ground Handling Systems
Maschinenbau Konrad Zaglauer

Tel. +49 (0) 8635 273

info@flyertruck.de

www.flyer-truck.com